



**INDUSTRIES LTD.**

***MODEL SF100-2PRV PACKAGED HYDRONIC SYSTEM FEEDER***

*The SF100-2PRV contains everything required to feed and pressurize two independent closed hydronic heating or cooling systems in a neat, simple package that is easy to install and operate. It is compatible with both water and water/glycol solutions.*



**FEATURES and BENEFITS**

- *Allows for independent pressure supply to a second system*
- *208 litre (55 US gallon) tank for storage and mixing*
- *Plugs into any standard 115 VAC outlet*
- *Fluid level switch shuts the pump off if the storage tank level gets low*
- *Accumulator tank prevents excessive pump cycling*
- *No direct connection to potable water supply eliminates need for backflow prevention*
- *Make-up fluid stored in the feeder tank can be pre-treated*
- *Diverter valve for purging of air on initial start-up and manual agitation of solution*
- *Prevents major floods - in the event of system rupture, only the contents of the tank can be pumped into the system*
- *Provides leak detection - dropping fluid level provides immediate notice that the system has developed a leak*
- *Fluid drained for service can easily be put back into the system*
- *Flexible connection hose with system check valve makes installation easy*

Represented By:

**AXIOM INDUSTRIES LIMITED** 2615 WENTZ AVENUE SASKATOON, SK S7K 5J1  
**TOLL FREE :** (877) 651-1815 **PHONE :** (306) 651-1815 **FAX :** (306) 242-3373

**www.axiomind.com**



# INDUSTRIES LIMITED

## SF100-2PRV HYDRONIC SYSTEM FEEDER TECHNICAL INFORMATION

**WEIGHT** - 16 kg, 35 lbs.

**ELECTRICAL**

115/60/1, 0.7 amps  
3-prong plug and cord

**PUMP PERFORMANCE**

0.09 l/s (1.4 gpm) @ free flow  
0.06 l/s (1.0 gpm) @ 345KPa (50 psig)  
Self-priming up to 2.1 m (7 feet)  
Maximum liquid temp. 77 C (170 F)



Certified to CAN/CSA  
C22.2 No. 68



9901055  
Conforms to UL73

**SPECIFICATION**

Hydronic system feeder shall be AXIOM INDUSTRIES LTD. Model SF100. System shall include 208 litre (55 US gallon) storage/mixing tank with cover; pump suction hose with inlet strainer; pressure pump with thermal cut-out; integral pressure switch; integral check valve; cord and plug; pre-charged accumulator tank with EPDM diaphragm; manual diverter valve for purging air and agitating contents of storage tank; two pressure regulating valves adjustable (35 – 380 KPa; 5 – 55 psig) complete with pressure gauges; integral replaceable strainer; built-in check valve; union connection; two 12 mm (1/2”) x 900 mm (36”) long flexible connection hoses with check valve; low level pump cut-out. Pressure pump shall be capable of running dry without damage. Power supply 115/60/1 0.7 A. Unit shall be completely pre-assembled and certified by a recognized testing agency to CSA standard C22.2 No 68.

**ACCESSORIES**

- RIA10-1-SAA** – Low Level Alarm Panel c/w Remote Monitoring Dry Contacts and Selectable Audible Alarm

**LIMITED WARRANTY**

The SF100-2PRV is warranted against defects in materials and workmanship for one year.

Project \_\_\_\_\_ Location \_\_\_\_\_  
Consultant \_\_\_\_\_ Contractor \_\_\_\_\_  
Unit Tag \_\_\_\_\_ Sales Agent \_\_\_\_\_